

▶ TECHNICAL INFORMATION

MINIMUM PULLEY DIAMETERS

BELT TYPE	TENSION								
	↘ 60%			30% - 60%			↗ 30%		
	P1	P2	P3	P1	P2	P3	P1	P2	P3
EP 250/2	250	200	160	200	160	125	160	160	125
EP315/2	250	200	160	200	160	125	160	160	125
EP400/3	315	250	200	250	200	160	200	200	160
EP500/3	400	315	250	315	250	200	250	250	200
EP630/3	500	400	315	400	315	250	315	315	250
EP630/4	500	400	315	400	315	250	315	315	250
EP800/3	630	500	400	500	400	315	400	400	315
EP800/4	630	500	400	500	400	315	400	400	315
EP800/5	630	500	400	500	400	315	400	400	315
EP1000/3	630	500	400	500	400	315	400	400	315
EP1000/4	800	630	500	630	500	400	500	500	400
EP1000/5	800	630	500	630	500	400	500	500	400
EP1250/3	800	630	500	630	500	400	500	500	400
EP1250/4	1000	800	630	800	630	500	630	630	500
EP1250/5	1000	800	630	800	630	500	630	630	500
EP1600/4	1000	800	630	800	630	500	630	630	500
EP1600/5	1250	1000	800	1000	800	630	800	800	630
EP2000/4	1250	1000	800	1000	800	630	800	800	630
EP2000/5	1250	1000	800	1000	800	630	800	800	630
EP2500/5	1600	1250	1000	1250	1000	800	1000	1000	800
EP3150/6	2000	1600	1250	1600	1250	1000	1250	1250	1000

P1: Drive and high-tension pulleys. **P2:** Tail pulleys. **P3:** Snub or bend pulleys where the change of direction does not exceed 30 degrees.